



SHINI color mixer series are the newly designed which doses and mixes color, additive, regrind and main material with great accuracy which suitable for all kinds of injection molding, extruder molding and blow molding machine, ensuring lower materials consumption and more consistent quality of the end product. Avoid having stocks of ready-mixed material while switching between different additives and color .

Feature:

1. Accuracy guarantees by P.I.D. controller within $\pm 0.1\%$.
2. The calibrating gate is designed for easy access.
3. DC brushless brush motor is used for maintenance free.
4. Equipped with indicator and alarm for the motor overload, and overheat .
5. No-tools are required for clean and maintenance.

規格表 Specifications

機型 / Model	SCM30-20	SCM30-16	SCM30-12	SCM100-20	SCM100-16	SCM100-12
電 壓 / Voltage	AC 220V $\pm 10\%$	AC 220V $\pm 10\%$	AC 220V $\pm 10\%$	AC 220V $\pm 10\%$	AC 220V $\pm 10\%$	AC 220V $\pm 10\%$
頻 率 / Frequency	50HZ/60HZ	50HZ/60HZ	50HZ/60HZ	50HZ/60HZ	50HZ/60HZ	50HZ/60HZ
馬達功率 / Motor Power	40W	40W	40W	40W	40W	40W
轉 速 / Motor Speed	0~3000RPM	0~3000RPM	0~3000RPM	0~3000RPM	0~3000RPM	0~3000RPM
儲料桶 / Hopper Volume(L)	10	10	10	10	10	10
機體重量 / Weight(KG)	15	15	15	15	15	15
減速比 / Gear Ratio	1:30	1:30	1:30	1:100	1:100	1:100
螺桿外径 / Screw Outside Diameter(mm)	20	16	12	20	16	12
輸出量 / Output Capacity(KG/hr)	3.12~24.18	1.86~18.78	1.02~6.96	0.96~7.44	0.78~5.76	0.30~2.16

备注：输出量不在以范围可特殊订制

Remark: This color mixer can be specifically made if the output capacity of your required is out of range on the above list.

